



**Type Number**..... 377  
**Designation IEC**..... SR66  
**System**..... Silver oxide/ Zinc /  
 NaOH - Electrolyte

**Nominal Voltage**..... 1,55 V  
**Typical Capacity C**..... 21 mAh  
 (47 kOhm continuous load at 20°C  
 down to 1,2 Volts)

**Weight (approx.)**..... 0,34 g  
**Volume**..... 0,09 ccm  
**Coding**..... Manufacturing Month/Year  
 by Letter Code

**Temperature Ranges** min max.  
 Storage..... 0°C 60°C  
 Discharge..... 0°C 60°C

**Dimensions** min max.  
 Diameter..... 6,6 mm 6,8 mm  
 Height (A/B)..... 2,4 mm 2,6 mm

**Segment**..... Watch

**Main Applications**..... Watch  
 Photo  
 Electronic

### Typical Capacities (at 20°C)

| Discharge Type            | Load    | End Voltage: 1.2V |           |
|---------------------------|---------|-------------------|-----------|
| Continuous<br>24h/d, 7d/w | 47000 Ω | Time:             | 710 hours |
|                           |         | Capacity          | 21 mAh    |
|                           |         | Energy :          | 30 mWh    |

**No publication or circulation of data to third parties without consent of VARTA Consumer Batteries**

All Data contained herein is for single cells For battery applications, performance data may vary from single cell data, depending on specific battery configuration