Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DC Supplier's address: Einkauf, Gewerbestraße 10, DE Model identifier: LED10MG4LKW Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source light source (CLS): Colour-tuneable light source: Nein Anti-glare shield: Nein Product parameters Parameter Parameter Value Parameters Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), 1,7 Standby power (Psb), expressed in W and rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperature, rounded to the ne	sources							
Model identifier: LED10MG4LKW Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light Nein source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W and rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) - Colour rendering 80	Supplier's name or trade mark: DC							
Type of light source: Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source: Nein Envelope: - High luminance light source: Nein Anti-glare shield: Product parameters Parameter Value Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W and rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W Networked standby power (Pnet) LED Non-directional or idirectional or idirectional or idirectional: Nein Dimmable: Only with specific dimmers Product parameters Value Parameter Valu	Supplier's address: Einkauf, Gewerbestraße 10, DE							
Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: Colour-tuneable light source: High luminance light source: Nein Anti-glare shield: Nein Product parameters Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) LED Non-directional or directional or directional: Ron-directional: Non-directional: Non-directional: Non-directional: Non-directional: Non-directional: Non-directional: Nein Non-expressed lin W Nein Dimmable: Only with specific dimmers Parameter Value General product parameters: Energy efficiency class F correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the second decimal	Model identifier: LED10MG4LKW							
Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source Nein Envelope: - High luminance light source: Nein Anti-glare shield: Nein Product parameters Parameter Value Parameter Value Parameter: Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) Networked standby power (Pnet) And Additional: Nein Nein Dimmable: Only with specific dimmers Parameter Value Parameter Value Parameter Value Parameter Value Parameter Value F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, roun	Type of light sour	rce:						
(or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Anti-glare shield: Nein Product parameters Parameter Value Parameter Value Parameter: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) Nein Enerology Connected light source: Nein Envelope: - Usling Envelope: - Usling Parameter Value Parameter Value Parameter Value Parameter Value Parameter: Energy efficiency class F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) - Colour rendering 80	Lighting technolog	gy used:	LED		NDLS			
Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Envelope: Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W On-mode power (Pon), expressed in W Networked standby power (Pnet) Networked standby power (Pnet) One ight source (CLS): Nein Envelope: - Useful product parameters Energy efficiency class F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the nearest 100 K, that can be set of correlated colour temperatures, rounded to the ne	Light source cap-t	type	G4					
Source (CLS): Colour-tuneable light source: High luminance light source: Anti-glare shield: Nein Product parameters Parameter Value Parameter Value Parameter: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) Nein Dimmable: Only with specific dimmers Parameter Value Parameter Value Parameter Value Parameter Value Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range	(or other electric	interface)						
High luminance light source: Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) Nein Dimmable: Only with specific dimmers Parameter Value Parameter Value Parameter Value F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) Networked standby power (Pnet) Only with specific dimmers Only with specific dimmers Only with specific dimmers Only with specific dimmers Nelworket shield: Nein Dimmable: Only with specific dimmers Only with specific dimmers Value Parameter Value F Correlated colour temperature, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) - Colour rendering 80	Mains or non-mains:		NMLS		Nein			
Anti-glare shield: Nein Dimmable: Only with specific dimmers	Colour-tuneable light source:		Nein	Envelope:	-			
Parameter Parameter Value General product parameters Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) Parameter Value Parameter Value Parameter Value Correlated Colour fficiency class Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) - Colour rendering 80	High luminance li	ght source:	Nein					
Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) Parameter Value Parameter Parameter Value Parameter Parameter F Colour rendering Value F Oalue F Colour rendering Value F Oalue F Colour rendering Value F Oalue F Colour rendering	Anti-glare shield:		Nein	Dimmable:	I			
Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) Page 190 in Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W Networked standby power (Pnet) On-mode po	Product parameters							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) Page 190 in Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set O,000 O,000 Energy efficiency F Oorrelated colour temperature, rounded to the nearest 100 K, that can be set O,000 Expressed in W and rounded to the second decimal Networked standby power (Pnet) - Colour rendering 80	Parameter		Value	Parameter	Value			
mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) Oscillated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) - Colour rendering 80	General product parameters:							
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) Sphere (360°) temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set O,000 O,000 temperature, rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set O the rounded to the nearest 100 K, that can be set	mode (kWh/1000 h), rounded up to the nearest integer		2	,	F			
expressed in W and rounded to the second decimal Networked standby power (P _{net}) - Colour rendering 80	indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone		Sphere (360°)	temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set				
	1 (0117)		1,7	expressed in W and rounded to the	0,00			
rounded to the second decimal the nearest integer, or the range of CRI- values that can be set	for CLS, expressed in W and rounded to the second decimal		<u>-</u>	index, rounded to the nearest integer, or the range of CRI- values that can be set				
OuterHeight30Spectral powerSee imagedimensionsWidth30distribution in the in last page					_			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	9	range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-		
			Chromaticity	0,311		
			coordinates (x and y)	0,336		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		5	Survival factor	0,90		
the lumen maintenance factor		0,70				

(a)نے : not applicable;

(b)_{'-'} : not applicable;

