




Technical Data Sheet

Date: 2021-05

Page: 1 of 1

Connection Boxes HAD 3 / HAD 3-F / HAD3 AP-BSP



Application	Wall-mounted box for connecting solid wire cables (fixed installation) to stranded wire cables (movable equipment). HAD3-AP-BSP equipped with glow wire resistant back cover for surface mounting onto flammable materials (e.g. wood).	
Standards	Boxes and enclosures for electrical accessories for household and similar fixed electrical installation. EN 60670-1:2014, EN 60670-22:2007	
Connection	Incoming: max 4 sqmm solid Outgoing: max. 2.5 sqmm stranded with ferrule Screw-type terminals	
No. of terminals	5 (3P, N, PE)	
Nominal voltage	400 V	
Test current EN 60670-22	24 A	
Mounting	HAD3 Flush mounting in combination with a dia. 60 mm one gang junction box or Surface mounting, 4 screws dia. 4 mm HAD3-F: Flush mounting in combination with a dia. 60 mm one gang junction box or HAD3 AP-BDP: Surface mounting, 4 screws dia. 4 mm	
IP code	IP 20, touch proof	
Dimensions w x h x d	HAD 3: 82,5 mm x 82,5 mm x 21 mm HAD 3-F: 81,5 mm x 81,5 mm x 12 mm	
Safety	rounded edges	
Environment	All materials and manufacturing processes comply with RoHS regulations	
Accessories	Z-HAD: strain relief for second outlet BSP-HAD. flame retardant back cover	