

# Ultimate Surfaces / Prestige

Current life span: 12/2027

STAR  
DESIGNSTAIN  
RESISTANT

COMPACTBACK

15 YEARS  
WARRANTY

## Technical information / Technische informatie - Information technique - Technische Daten

|                                                                                                                                                                                  |                      |                                              |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----------------------------------------------|
| <b>Usage class</b> / Gebruiksklasse - Classe d'usage - Eignungsklasse                                                                                                            | EN ISO 10874         | 23 - 32                                      |
| <b>Total thickness</b> / Totale dikte - Epaisseur totale - Gesamtdicke                                                                                                           | EN ISO 24346         | ca. 2.80 mm                                  |
| <b>Wear layer</b> / Slijtlaag - Couche d'usure - Nutzschicht                                                                                                                     | EN ISO 24340         | ca. 0.35 mm                                  |
| <b>Wear layer treatment</b> / Behandeling slijtlaag - Traitement couche d'usure - Schutz vor Schmutz                                                                             |                      | PU lacquer                                   |
| <b>Total weight/m<sup>2</sup></b> / Totaal gewicht/m <sup>2</sup> - Poids total/m <sup>2</sup> - Gewicht/m <sup>2</sup>                                                          | EN ISO 23997         | ca. 1800 g/m <sup>2</sup>                    |
| <b>Width</b> / Breedte - Largeur - Breite                                                                                                                                        |                      | 2 - (3) - 4 m                                |
| <b>Standard length</b> / Standaardlengte - Longueur standard - Standardlänge                                                                                                     |                      | ca. 30 - (30) - 30 m                         |
| <b>Weight of standard roll</b> / Standaard rolgewicht - Poids standard des rouleaux - Standardrollengewicht                                                                      |                      | ca. 108 - (162) - 216 kg                     |
| <b>Inflammability</b> / Brandklasse - Classement feu - Brandverhalten                                                                                                            | EN 13501-1           | Cfl-S1                                       |
| <b>Slip resistance</b> / Antislip - Glissance - Rutschfest                                                                                                                       | EN 13893             | DS                                           |
| <b>Slip restraint</b> / Slipweerstand - Résistance au glissement - Rutschemmung                                                                                                  | EN 16165<br>Annex B  | R10 - R11**                                  |
| <b>Thermal conductivity</b> / Thermische geleidbaarheid - Conductivité thermique - Wärmeleitfähigkeit                                                                            | ISO 8302 (1991)      | 0.073 - 0.119 W/(m.K)                        |
| <b>Heat insulation</b> / Thermische isolatie - Isolation thermique - Wärmedurchlasswiderstand                                                                                    | EN 12667:2001-01     | 0.007 - 0.066 m <sup>2</sup> .K/W            |
| <b>Acoustic insulation</b> / Contactgeluidsisolatie - Isolation acoustique - Trittschallverbesserungsmaß                                                                         | EN ISO 717-2         | 18 dB                                        |
| <b>Underfloor heating</b> / Vloerverwarming - Chauffage par le sol - Fußbodenheizung                                                                                             | EN 12524<br>EN 12667 | Suitable - Geschikt<br>Adapté - Geeignet     |
| <b>Resistance to household chemicals</b> / Bestendigheid tegen huishoudelijke chemicaliën<br>Résistance aux produits d'entretien domestiques - Haushaltschemikalienbeständigkeit | EN ISO 26987         | Very good - Zeer goed<br>Très bon - Sehr gut |
| <b>Warranty years</b> / Garantie in jaren - Durée de la garantie en années - Garantie Jahren                                                                                     |                      | 15                                           |

\*\* depending on the type of texture

The warranty covers manufacturing defects and early wear due to normal residential use. / Wij bieden u garantie tegen fabrieksfouten en vroegtijdige slijtage bij normaal residentieel gebruik.

La garantie couvre les erreurs de fabrication et l'usure précoce lors d'un emploi normal résidentiel. / Die Garantie gewährleistet Fabrikationsfehler und frühzeitiges Abnutzen in normalen Wohnbereich.

