

Parquet range with hardwood top layer

Range	Parquet Skandor
-------	-----------------

Product details

	3-strip
Dimensions in mm (L * B * D)	1182 x 200 x 11
Wear layer	approx. 2,5 mm
Packing	8 planks
Package	1,891 sqm, 12,34 kg
Warranty	15 years for domestic use according to our separate terms of warranty
Profile	ClickTec
Notes	Technical changes reserved. Cleaning and maintenance according to our separate instructions.

Product construction

Wear layer	hardwood
Middle layer	softwood staves *
Stabilizing layer	softwood veneer

* HDF-board-inserts at each end for profiling

Product properties

	Test standard	
Thermal resistance	DIN EN 4108-4	0,078 sqm K/W
Thermal conductivity	EN 12664	≥ 0,091 W/(m*K)
Biological durability		Class 1
PCP-content		< 5 ppm
Formaldehyde	EN 717 - 2	Class E1
Reaction to fire	EN 13501-1	Dfl-s1
Resistance to chair castors	DIN EN 13329	No impact if soft chair castors are used.
Grading specifications	EN 13489	Request are fulfilled by manufacturing gradings.
Laying system (laying procedure)	EN 13489	floating, overall glued
floor heating (underfloor heating)		Only suitable for hot water underfloor heating with a maximum surface temperature of 29°.
Renovation		Min. 2x sanding with normal wear
Disposal		Private disposal with regular household garbage / bulk waste possible

Tolerances to EN 13489

Allowed differences in width	± 0,2 mm
Allowed variation of squareness	≤ 0,2 %
Longitudinal curvature (along the element)	≤ 0,1 %
Transverse wrapping	≤ 0,2 %
Height differences (between the elements)	≤ 0,2 mm
Wood moisture at the time of first delivery	5-9%

Surface properties

	Test standard	
Slip resistance	EN 15676	Lacquer
Stain resistance	DIN 68861 - 1	USRV 70
Scratch resistance	Hamberger Hobel	1B
		≥ 20 N

Product labels

		
---	---	---