



Parquet range with hardwood top layers	
Assortment	

Product details		
	plank	plank
Dimensions in mm (L * W * T)	2190 x 162 x 12	1082 x 162 x 12
Wear layer	2,5 mm	2,5 mm
Packaging	6 Panels	6 Panels
Package	2,129 m ² , 20,55 kg	1,052 m ² , 10,28 kg
Warranty	15 years for domestic use in accordance with the warranty conditions	15 years for domestic use in accordance with the warranty conditions
Profile	Click system	
Notes	to technical changes, see instructions for cleaning	

Product construction		
Wear layer	Hardwood	Hardwood
Middle layer	HDF	HDF
Stabilizing layer	Kraft paper	Kraft paper

Product properties			
	Test standard		
Thermal resistance	DIN EN 4108-4	0,096 m ² K/W	0,096 m ² K/W
Thermal conductivity	EN 12664	0,13 W/(m*K)	0,13 W/(m*K)
PCP-content	CEN/TR 14823	$\leq 5 \cdot 10^{-6}n$	
Formaldehyde	EN 717 - 1	E1	
Reaction to fire	EN 13501-1	Dfl-s1	
Resistance to chair castors	DIN EN 13329	No change if soft chair castors are used	
Grading specifications	EN 13489	Grading according to factory requirements	
Type of installation	EN 13489	table for floating installation or glue down installation	
Underfloor heating		water underfloor heating systems. The surface temperature must not exceed 27°C	
Renovation		Min. 2x sanding with normal wear	
Disposal		Private disposal with regular household waste	

Tolerances according to EN 13489

Permissible broom deviation	$\pm 0,2 \text{ mm}$
Permissible deviation from perpendicularity	$\leq 0,2 \%$
Longitudinal curvature (along the element)	$\leq 0,1 \%$
Transverse curvature (via the element)	$\leq 0,2 \%$
Overtooth (between the elements)	$\leq 0,2 \text{ mm}$
Wood moisture content at the time of initial delivery	5-9%

Surface properties

	Test standard	oxidative natural oil	Natural oil planed
Slip resistance Pendulum value	EN 15676	USRV 109	USRV 64
Slip resistant properties	DIN 51130	R11	USRV 64
Stain resistance	DIN 68861 - 1	1C	1C
Scratch resistance	Hamberger Hobel	n.n	n.n

Product labeling



www.realwood.eu