



TECHNICAL SHEET



FA 20 501 06


Designation: Retractable Fall Arrester Olympe-S in webbing

- Webbing width 25 mm.
- Casing made up of high impact strength Polymer to prevent breakage, and nearly indestructible.
- Braking system integrated in the casing.
- Swivel at the top and at the bottom of the device.
- Minimum breaking strength: > 15 kN.
- External energy absorber for horizontal use.

Connectors: 1 steel screw-locking karabiner opening 17 mm, ref. FA 50 101 17 and 1 steel snap hook with swivel fall indicator, opening 21 mm, ref. FA 50 203 20 on the webbing.

Compliance: EN 360:2002.

Tested and approved for horizontal use according to VG 11.060 (rev. 7 – 06/2013).



Length: 6 mtrs.

Material of components:

Protective casing: PA 6 30% fiberglass.

Webbing: Polyester.

Connector: Steel.

HS code

84289090

Carton size / Pieces

60 x 40 x 24 cm / 4

Unit weight

2.65 Kg

AET : N° Issue Extension

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 04/16

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

