



# Gardentop Stick Alu 5 x 1m

V01.r1/2023

Item number: 71060215, EAN: 5420004312612, Color: silver grey

## APPLICATION

*This roofing membrane is suitable for almost all slightly sloping roofs (min. roof slope 3° or 5.2%). Ideal for garden house, carport and secondary outbuildings <30 m². Gardentop Stick Alu adheres to constructions of wood, metal, bitumen, concrete, masonry, and plastic (except PVC). Does not adhere to silicone.*

## FINISHING

Finish upper face:

UV-resistant composite aluminium layer

Finish lower face:

silicone film

## DIMENSIONS

Length x Width (EN 1848-1):

5 x 1 m

Thickness (EN 1849-1):

1,1 mm

Weight/Roll:

± 6 kg (± 6,6 kg, box included)

## PACKING

1 roll per box

20 boxes per pallet

## TECHNICAL INFORMATION

Tensile strenght (EN 12311-1)

≥ 200N

Flow resistance at 80°C (EN 1110)

< 2 mm

Water vapour transmission Sd

> 1500 m

Reaction to fire (EN 13501-1)

F

## APPLICATION

Application temperature:

+12°C / +35°C

*The bitumen adhesive is thermoplastic: at low temperatures, the strength increases, at high temperatures the mass becomes softer. At the same time, the surface stickiness becomes significantly stronger with increasing temperatures.*

*Dimensional stability from -20°C to +70°C*

## HANDLING AND STORAGE

*Store the material in the outer packaging in a dry, light-protected place at room temperature. Protect against mechanical damage. At high outside temperatures, the membrane should be stored in the shade. The removal of the protective layer can be complicated by an increased temperature of the material. The substrate should be dry, free of dust, resin (especially pine or from other types of wood), and grease and be wear-resistant. Impregnated wood should first be sufficiently hardened so the adhesive surface of the roll is not affected. The installation temperature should be min. 12 °C. Store the roofing membrane in a heated room before installation when the weather is cold. An optimal adhesive strength can be obtained at higher temperatures. Recommended processing period: 12 months after production.*

IKO Sales International NV

I.Z. Ravenshout 3.9 74 • Truibroek 74

3945 Ham • Belgium

E residential.europe@iko.com

Sales support:

T +32 (0)11 34 01 82

F +32 (0)11 34 01 30

Order desk:

T +32 (0)11 34 01 34

F +32 (0)11 34 13 19



www.iko.be