




Made in China

SAFETY INSTRUCTIONS

- ① Please read the instructions carefully before using
- ① Do not disassemble or refit the products.
- ① Press touch sensor button properly.
- ① Keep the mirror dry, moisture reduces the sensitivity of the product.
- ① Turn off the power before cleaning. The surface of the mirror should be cleaned with glass cleaner, please make sure the mirror is completely dry before using.
- ① Turn off the power and avoid direct sunlight if not used or stored for a long time. Far away from children's access.
- ① Make sure that your charging device is adequate for the mirror voltage rating before using.
- ① Do not approach or put the product into the fire in case of fire or explosion.
- ① Stop using it immediately if abnormal condition occurs.


LED Bathroom Mirror WITH BLUETOOTH OPERATING MANUAL



SPECIFICATIONS

Beliani(International) GmbH ITEM NO.:36096
Haldenstrasse 5
6340 Baar
Switzerland

INPUT:AC220V,50/60HZ
Power:51W+10%
LED Mirror



PACKING LIST



LED Bathroom Mirror with Bluetooth



Instruction Manual

* We reserves the right of any modification of the product involving design and specification, all the materials here are for your reference only and are subject to the products you received. No further notice be given for any technical parameters changed.

OPERATING INSTRUCTIONS



1. Press ④ to start work. 5 second later, display show current temperature and time.
Short press ④ to open anti-fog function,long press ④ 3 second to finish work.
2. Press ① control light on/off.press ② to open bluetooth speaker function.after the speaker emits a "beep",open bluetooth function of phone,search and connect the products.
3. Press ① to ② to choose the songs during playing music.
4. Press the ① ② open the volume set,then press the ① or ② while the volume is flashing to adjust the volume.Long press ④ 3 seconds to turn off Bluetooth playback.
5. Long Press ④ for 3 second to enter date and time adjustment.Then press ① or ② to adjust date while number is flashing,when adjustment completed,press button ④ to move to next step.After all the settings are complete,wait for 5 second to return to normal work.