

SAFETY INSTRUCTION

Please study the instruction manual and below information carefully before installing or using this product.
Please keep this user manual for further reference.

1. The luminaires may only be installed by authorized and qualified technicians according the valid regulations for electrical installation.
2. Maintenance of the luminaires is limited to their surfaces. During maintenance no moisture can come into contact with any areas of the terminal connections or voltage control parts.
3. The electrical supply must be switched off at the outset, preferably by means of a switch in the distribution box, before any installation, maintenance or repair work is undertaken.
4. Exterior lighting must not be installed during rain.
5. Take account of the minimal separation distance from other objects and the room required around the fitting.
6. If in any doubt, consult a professional, taking local installation requirements into account. Some countries stipulate that lighting may be installed only by registered installers.
7. Clamping screws in electrical connections must be adequately tightened. This is particularly the case with 12V low voltage conductors.
8. Clean with a clean, dry cloth or brush, use no solvents or abrasives. Avoid dampness on all electrical components.
9. Take account of all available technical information.
10. Meaning of symbols:



This icon indicates the level of water-proof and dust-proof



Protection Class I: the fitting must be earthed



Protection Class II: the fitting is doubled insulated and does not require earthing



Protection Class III: the fitting is low voltage



Minimum distance from lighted objects (meters)



The type of lamp and maximum size and wattage indicated in each lighting unit must not be exceed; different items require different kind of light sources with different bulb icons



220-240V 50Hz The armature is designed to work only with the indicated voltage. Different items require different working voltage.



The luminaire can be used in combination with a dimmer



The luminaire can be dimmed by wall switch




The reference light angle and light space of the luminaire



This luminaire cannot be disposed together with normal domestic waste in standard rubbish can, but you have to bring it to a staging area for electrical waste

11. Take note of the symbols when connecting wires:



	(DE)	(GB)	(FR)	(NL)	(PL)	(NO)	(DK)
L	Stromführender Leiter	Live-conductor	Conducteur	Spannungsvoerende draad	Przewód prądowy	Strømførende ledet	Strømførende ledet
	Schutzleiter	Earth conductor	Conducteur de protection (tern)	Aardkabel	Priewód uziemiający	Jordledningen	Jordledningene
N	Neutralleiter	Neutral conductor	Conducteur neutre	Nullader	Przewód zerowý	Neutralleder	Neutralleder

	(SE)	(FI)	(IT)	(ES)	(CZ)	(PT)	(GR)
L	Södertörnande ledare	Virtajohdin	Condutore sotto tensione	Conductor de corriente	Vodič pod napětím	Condutor vivo	Πουλαρός αγωγής
	Skyddssledare	Suojaohdin	Conduttore di terra	Conductor de protección	Ochranný vodič	Conductor de terra	Αγωγή γης
N	Neutralledare	Nollajohdin	Conduttore neutro	Conductor neutro	Neutralní vodič	Condutor neutro	Ουδέτερος αγωγής

INSTRUCTION MANUAL

(NL) Gebruikte symbolen

(GB) Safety Precautions / (FR) Symboles utilisés / (DE) Verwendete Symbole / (PL) Stosowane symbole / (NO) Brukte symboler /

(DK) Brugte symboler / (SE) Använda symboler / (FI) Käytetyt symbolit / (IT) Simboli usati / (ES) Simblos empleados

(CZ) Použité symboly / (PT) Símbolos utilizados / (GR) Χρησιμοποιούνται σύμβολα



220-240V~
50Hz

Max. ø45mm
2x E27 Max. 40W

IP20

CE

UK
CA



Kasbah HL 50 Gold 97801

WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.

Assembly:

1. Shut off main electrical supply.
2. & 3. Use screws to mount the bracket on the ceiling.
4. Connect the electrical cable provided with the lamp with the mains wire.
5. Install the ceiling canopy on the mounting bracket using the two canopy screws.
6. This lamp has a centre body comprising of 2 lamp holders which takes 2x E27 Bulbs. Install the 2 bulbs on the lamp holders.
7. Carefully use the set screws provided with the lamp to install the Crystal fitting on the top gallery.
8. Once the fitting is complete as shown in the below image, power on the Chandelier for use.

